

# Complete One テクニカルデータ (MFH-25+ ヘッドケーブル 5m 使用)

## 対称(SINGLEモード)

	A	B	C
1灯	1200	—	—
1灯	—	1200	—
1灯	—	—	1200
2灯	600	600	—
2灯	—	600	600
2灯	600	—	600
3灯	400	400	400

## 非対称(MULTIPLEモード)

	A	B	C
1灯	800	—	—
1灯	—	400	—
1灯	—	—	400
2灯	400	400	—
2灯	—	400	400
2灯	800	—	400
3灯	400	400	400

## Colorモード(Full~1/64を1/10EVステップ)

	表示	閃光速度	色温度
Full	1200	1/190	5430
	900	1/190	5460
1/2	600	1/220	5480
	450	1/380	5490
1/4	300	1/500	5520
	225	1/380	5400
1/8	150	1/790	5430
	100	1/790	5470
1/16	75	1/1000	5510
	50	1/790	5400
1/32	38	1/1000	5440
	25	1/1300	5460
1/64	19	1/1800	5480

	表示	閃光速度	色温度
Full	800	1/260	5400
	600	1/260	5420
1/2	400	1/310	5470
	300	1/480	5500
1/4	200	1/690	5510
	150	1/480	5420
1/8	100	1/690	5440
	75	1/970	5490
1/16	50	1/1300	5530
	38	1/970	5430
1/32	25	1/1300	5460
	19	1/1700	5490
1/64	13	1/2250	5500

	表示	閃光速度	色温度
Full	600	1/290	5390
	450	1/290	5440
1/2	300	1/380	5460
	225	1/560	5500
1/4	150	1/800	5520
	112	1/560	5440
1/8	75	1/800	5470
	70	1/430	5350
1/16	50	1/560	5370
	25	1/1150	5450
1/32	19	1/1550	5470
	14	1/2100	5470
1/64	9	1/2900	5520

	表示	閃光速度	色温度
Full	400	1/390	5370
	300	1/390	5420
1/2	200	1/500	5460
	150	1/390	5320
1/4	100	1/460	5430
	75	1/700	5440
1/8	50	1/1000	5510
	38	1/800	5400
1/16	25	1/1100	5450
	19	1/1450	5460
1/32	13	1/2000	5500
	8.5	1/2600	5510
1/64	6	1/3400	5530

## Speedモード(Full~1/128を1/10EVステップ)

	表示	閃光速度	色温度
Full	1200	1/190	5430
	900	1/190	5460
1/2	600	1/220	5480
	450	1/380	5490
1/4	300	1/540	5510
	225	1/790	5530
1/8	150	1/1000	5550
	100	1/1300	5590
1/16	75	1/1800	5640
	50	1/2400	5690
1/32	38	1/3100	5760
	25	1/3800	5830
1/64	19	1/4800	5920
	14	1/5900	6040
1/128	9	1/7200	6290

	表示	閃光速度	色温度
Full	800	1/260	5400
	600	1/260	5430
1/2	400	1/310	5460
	300	1/480	5490
1/4	200	1/690	5510
	150	1/970	5520
1/8	100	1/1300	5570
	75	1/1700	5610
1/16	50	1/2250	5680
	38	1/3000	5730
1/32	25	1/3700	5800
	19	1/4600	5920
1/64	13	1/5600	6030
	8.5	1/7000	6210
1/128	6	1/8200	6530

	表示	閃光速度	色温度
Full	600	1/290	5370
	450	1/290	5420
1/2	300	1/380	5470
	225	1/560	5490
1/4	150	1/800	5510
	112	1/1150	5540
1/8	75	1/1550	5570
	50	1/2100	5620
1/16	38	1/2900	5690
	25	1/3300	5770
1/32	19	1/4100	5870
	14	1/5300	5960
1/64	9	1/6700	6120
	6.5	1/7700	6440
1/128	4	1/9000	6630

	表示	閃光速度	色温度
Full	400	1/390	5360
	300	1/390	5420
1/2	200	1/500	5460
	150	1/800	5500
1/4	100	1/1100	5530
	75	1/1450	5570
1/8	50	1/2000	5620
	38	1/2600	5670
1/16	25	1/3400	5750
	19	1/4400	5860
1/32	13	1/5200	5960
	8.5	1/6500	6150
1/64	6	1/7800	6470
	4.5	1/9700	6760
1/128	3	1/11000	7060